Basic Vector Styling

QGIS Tutorials and Tips

Ujaval Gandhi ujaval@qgistutorials.com

Basic Vector Styling

To create a map, one has to style the GIS data and present it in a form that is visually informative. There are a large number of options available in QGIS to apply different types of symbology to the underlying data. In this tutorial, we will explore some basics of styling.

Overview of the task

We will style a vector layer to show life expectancy in different countries of the world.

Other skills you will learn

• View the attribute table of a vector layer.

Get the data

The data we will use is from Center for Sustainability and the Global Environment (SAGE) at the University of Wisconsin-Madison.

You can download the Life Expectancy GIS Grid data from the human impact dataset. For convenience, you can also download a copy of this data by clicking on following link:

lifeexpectancy.zip

Procedure

1. Open QGIS and go to Layer • Add Vector Layer...

X				QGIS	2.0.1	-Dufo	bur							-	. • 💻	×
P <u>r</u> oject	<u>E</u> dit	<u>V</u> iew	Layer Settings Plugins Vector Raster Da	tabase	Help)										
			New Embed Layers and Groups	P	(1:1)	200	Ç	\square	\mathcal{A}	\mathcal{A}	3		<u>,</u>	- 2	* * * * • • • • • • • • • • • • • • • •	»
ŧ.			Voit Add Vector Layer Ctrl+Shift+V Image: Ctrl+Shift+R Ctrl+Shift+R	abc	aby	abr	(abc	abc	abc	abc						
ຊ່ວວ		ana I	📭 Add PostGIS Layers Ctrl+Shift+D													
٧œ			Add SpatiaLite Layer Ctrl+Shift+L													
			Add MSSQL Spatial Layer Ctrl+Shift+M													
m			Add Oracle Spatial Layer Ctrl+Shift+O													
~			Add WMS/WMTS Layer Ctrl+Shift+W													
Pa			Add WES Laver													
			 Add Delimited Text Laver 													
10			Copy style													
Q.			Paste style													
			Open Attribute Table													
00			🥢 Toggle Editing													
			🔛 Save Layer Edits													
979			// Current Edits													
-0			Save As													
20			Save Selection as Vector File													
V° -			Duplicate Layer(s)													
L • 🔝			Set CRS of Layer(s) Ctrl+Shift+C													
			Set Project CRS from Layer													
			Properties													
\\Ä			Query													
	I		Labeling	102.0	-110 5			Scale		26672		SV 🖌 🛛	ender	EDSG-432	5	1
			Add to Overview	102.0	,-119.3	,		Jocale	[:24:	130072	Ľ		enuer	L-30,432] //

See more tutorials at http://qgistutorials.com

2. Browse to the downloaded *lifeexpectancy.zip* file and click Open. When prompted, select *WGS84 EPSG:4326* as the Coordinate Reference System (CRS).

Coordinate Reference	System Selector ? ×
Specify CRS for layer lifeexpectancy	
Filter	
Recently used coordinate reference systems	5
Coordinate Reference System	Authority ID
North_Pole_Azimuthal_Equidistant	EPSG:102016
OSGB 1936 / British National Grid	EPSG:7405
Unknown datum based upon the Everest 183	EPSG:4044
WGS 84 / Pseudo Mercator	EPSG:3857
WGS 84	EPSG:4326
•	
Coordinate reference systems of the world	Hide deprecated CRSs
Coordinate Reference System	Authority ID
WGS 66	EPSG:4760
WGS 72	EPSG:4322
WGS 72BE	EPSG:4324
WGS 84	EPSG:4326
WGS72	_IGNE:WGS72G
<u> </u>	
Selected CRS: WGS 84	
toroi-longiat tdatum-WGS84 too defa	
Tproj-longiat Tuatum-W050T Tho_dels	
	OK Cancel Help
	N

3. The shapefile contained within the zip file is now loaded and you can see the default style applied to it.



4. Right click on the layer name and select Open Attribute Table.



5. Explore the different attributes. To style a layer, we must pick an *attribute* or a *column* that would represent the map we are trying to create. Since we want to create a layer represting life expectancy, i.e. the average age till a person lives in a country, the field LIFEXPCT is the attribute we want to use in styling.

ø	A	Attribute table -	newsweek_data	a :: Features tota	al: 165, filtered:	165, selected: 0		×
		E 😼 📰	💁 😻 🞾			\frown		?
	GRWRATE	URBPOP	MIG_RATE	POP_15	POP65_ (LIFEXPCT		
0	2.62000000	47.00000000	0.00000000	45.20000000	3.80000000	47.00000000	7.00000000	:::
1	2.66000000	33.00000000	0.00000000	44.90000000	3.10000000	42.00000000	4.00000000	
2	1.90000000	53.00000000	-0.40000000	33.20000000	5.10000000	76.00000000	58.00000000	
3	0.94000000	35.00000000	-9.90000000	32.30000000	4.00000000	65.00000000	31.00000000	
4	3.32000000	46.00000000	2.20000000	46.00000000	3.70000000	55.00000000	6.00000000	
5	3.17000000	44.00000000	0.50000000	48.10000000	2.80000000	52.00000000	1.00000000	
6	3.36000000	32.00000000	-0.10000000	48.00000000	2.50000000	50.00000000	8.00000000	
7	3.40000000	5.00000000	0.70000000	49.80000000	2.30000000	46.00000000	10.00000000	
8	2.88000000	8.00000000	0.00000000	46.30000000	2.90000000	48.00000000	9.00000000	
9	3.72000000	29.00000000	-0.20000000	47.10000000	2.90000000	46.00000000	1.00000000	
10	2.84000000	49.00000000	-0.10000000	48.50000000	2.20000000	49.00000000	1.00000000	
11	3.31000000	15.00000000	-7.70000000	49.20000000	2.60000000	45.00000000	7.00000000	
12	2.37000000	51.00000000	-0.10000000	39.70000000	3.90000000	59.00000000	30.00000000	
13	2.83000000	27.00000000	32.00000000	44.90000000	3.30000000	47.00000000	4.00000000	
14	2.97000000	25.00000000	-0.30000000	44.60000000	2.80000000	60.00000000	43.00000000	
15	3.180000000	33.00000000	0.00000000	45.00000000	3.40000000	58.00000000	26.00000000	
16	1.550000000	84.00000000	0.00000000	30.50000000	6.40000000	72.00000000	43.00000000	
17	2.92000000	25.00000000	0.00000000	44.90000000	3.30000000	68.00000000	33.00000000	
18	2.69000000	46.00000000	0.00000000	39.60000000	3.60000000	67.00000000	48.00000000	
19	2.37000000	60.00000000	0.20000000	37.50000000	4.00000000	62.00000000	48.00000000	
20	2.68000000	30.00000000	0.00000000	42.50000000	3.10000000	57.00000000	20.00000000	
21 ◀	2 47000000	000000000	0.00000000	40.70000000	3 900000000	56.000000000	5 00000000	
	Show All Features							

6. Close the attribute table. Right click on the layer again and choose Properties.



7. The various styling options are located in the Style tab of the Properties dialog. Clicking on the drop-down button in the Style dialiog, you will see there are five options available - Single Symbol, Categorized, Graduated, Rule Based and Point displacement. We will explore the first three in this tutorial.

ø	Layer Properties -	newsweek_data ? ×
General Style abc Labels Fields Display Actions Joins Diagrams Image: Actional state	Style Layer rendering Layer transparency Layer blending mode Normal Single Symbol Categorized Graduated Rule-based Point displacement Symbol layers Fill Simple fill	Feature blending mode Init Milimeter Transparency 0% Color Saved styles Image: Corners diagonal dotted green land Image: Corners diagonal dotted green land
Restore Default Style	e Save As Default	Load Style Save Style 🔻
		OK Cancel Apply Help

8. Select Single Symbol. This option allows you to choose a single style that will be applied to all the features in the layer. Since this is a polygon dataset, you have two basic choices. You can *fill* the polygon, or you can style with only *outline*. You can choose the dotted pattern fill and click OK.

M.	Layer Properties -	newsweek_data	×
Image: Constraint of the second sec	Style	Feature blending mode Image: Vector of the sector of	
		dotted Symbol Advanced	•
Restore Default Style	Save As Default	Load Style Save Style	•
		OK Cancel Apply Help	

9. You will see a new style applied to the layer with the fill pattern you chose.



10. You will see that this Single Symbol style isn't useful in communicating the life expectancy data we are trying to map. Let us explore another styling option. Right-click the layer again and choose Properties. This time choose Categorized from the Style tab. Categorized means the features in the layer will be shown in different shades of a color based on unique values in an attribute field. Choose LIFEXPCT value as the Column and click Classify at the bottom. Click OK.

<u>N</u>	Layer Properties - newsweek_data	? ×
General Style Cabels Fields	Style Layer rendering Layer transparency Layer blending mode Normal Feature blending mode Normal Categorized Categorized 	0 🔹
Display	Column LIFEXPCT Symbol Change Color ramp Blues	•
Joins Diagrams Toing Metadata	Symbol Value Label -99 -99 39 39 42 42 43 43 44 44 45 45 46 46 47 47 48 48 49 49 50 50 51 51 52 52 53 53 54 54 55 55 56 56 Classify Add Delete Delete all	
Restore Default Style	e Save As Default Load Style Save Style	•
	OK Cancel Apply	Help

11. You will see different countries appearing in shades of blue. Lighter shades meaning lower life expectancy and darker shades meaning higher life expectancy. This representation of the data is more useful and clearly show how life expectancy in developed countries vs. developing countries. This would be the type of style we set out to create.



- 12. Let us explore the Graduated symbology type in the Style dialog now. Graduated symbology type allows you to break down the data in a column in unique *classes* and choose a different style for each of the classes. We can think of classifying our life expectancy data into 3 classes, *LOW*, *MEDIUM* and *HIGH*. Choose LIFEXPCT as the Column and choose 3 as the classes. you will see there are many Mode optionsavailable. Let us see the logic behind each of these modes. There are 5 modes available. Equal Interval, Quantile, Natural Breaks (Jenks), Standard Deviation and Pretty Breaks. These modes use different statistical algorithms to break down the data into separate classes.
 - Equal Interval: As the name suggests, this method will will create classes which are at the same size. If our data ranges from 0-100 and we want 10 classes, this method would create a class from 0-10, 10-20, 20-30 and so on , keeping each class the same size of 10 units.
 - Quantile This method will decide the classes such that number of values in each class are the same. If there are 100 values and we want 4 classes, quantile method will decide the classes such that each class will have 25 values.
 - Natural Breaks (Jenks) This algorithm tries to find natural groupings of data to create classes. The resulting classes will be such that there will be maximum variance between individual classes and least variance within each class.
 - Standard Deviation This method will calculate the mean of the data, and create classes based on standard eviation from the mean.
 - Pretty Breaks This is based on the statistical package R's pretty algorithm. It is a bit complex, but the *pretty* in the name means it creates class boundaries that are round numbers.

To keep things simple, let's use the Quantile method. Click Classify at the bottom and you will see 3 classes show up with their corresponding values. Click OK.

Note

For an attribute to be used in Graduated style, it must be a numeric field. Integer and Real values are fine, but if the attribute field type is String, it cannot be used with this styling option.

я́	Layer Properties - newsweek_data ? ×
General Style Cabc Labels	Style Layer rendering Layer transparency Layer blending mode Normal Feature blending mode
Fields	Column LIFEXPCT
Actions	Symbol Change Classes Classes Mode Quantile (Equal Count) V
Diagrams	Symbol Value Label -99.0000 - 55.6667 -99.0000 - 55.6667 55.6667 - 70.0000 55.6667 - 70.0000 70.0000 - 79.0000 70.0000 - 79.0000
	Classify Add dass Delete Delete all Advanced
Restore Default Style	Save As Default Load Style Save Style

13. You will see a map showing countries in either of 3 colors representing average life expectancy in the country.



14. Now go back to the Style dialog by right clicking the layer and choosing Properties. There are some more styling options available. You can click on the Symbol for each of the classes and choose a different style. We will choose Red, Yellow and Green fill colors to indicate low, medium and high life expectancy.

Style Style Layer rendering Layer transparency Layer blending mode Normal Fields Column LIEP.PCT Actons Symbol Color ramp Soins Color ramp Isource Mode Quantie (Equal Count) Pagrams Pagrams Stedata Stedata Classefy Add dass Delete Delete all	я́	Layer Properties - newsweek_data	? ×
Style Layer transparency Layer blending mode Normal Fields Column Display Column Color ramp Symbol Color ramp Symbol Symbol Symbol Symbol Symbol Color ramp Symbol	General	Style Layer rendering	
Index Layer blending mode Normal Fields Display Column LIFEXPCT Image: Column Color ramp Color ramp Color ramp Color ramp Image: Color ramp	😻 Style	Layer transparency	0
Fields Column LIFEXPCT Classes Actions Symbol Color ramp [source] Mode Quantile (Equal Count) Mode Quantile (Equal Count) Mode Quantile (Equal Count) Note Paper Note Paper	(abc) Labels	Layer blending mode Normal Feature blending mode Normal	-
Isplay Column IFEXPCT Isplay Symbol Change Classes 3 Isplay Isplay Isplay Symbol Color ramp Isplay Isplay <td>Fields</td> <td>Craduated 💌</td> <td></td>	Fields	Craduated 💌	
Actions Symbol Ioins Color ramp Image: Diagrams Image: Operation of the symbol Image: Operation of the symbol <td>🤛 Display</td> <td>Column LIFEXPCT 🗸</td> <td></td>	🤛 Display	Column LIFEXPCT 🗸	
Joins Color ramp Diagrams Image: String in the	Actions	Symbol Change Classes 3	-
Diagrams Impl Value Label Impl Value 199,0000 - 55,6667 - 99,0000 55,6667 - 70.0000 Impl Value 199,0000 - 55,6667 - 70.0000 55,6667 - 70.0000 Impl Value 199,0000 - 79,0000 55,6667 - 70.0000 Impl Value 199,0000 - 55,6667 - 70.0000 55,6667 - 70.0000 Impl Value 199,0000 - 79,0000 55,6667 - 70.0000 Impl Value 100,000 - 79,0000 70.0000 - 79,0000 Impl Value 100,000 - 79,0000 100,000 - 79,0000 Impl Value	Joins	Color ramp [source] Mode Quantile (Equal	Count) 🔻
image: style style style image: style style style style image: style style style style style style style image: style	Diagrams	Symbol 🗸 Value Label	
Classify Add class Delete all Advanced •	🥡 Metadata	-99.0000 - 55.6667 -99.0000 - 55.6667 55.6667 - 70.0000 55.6667 - 70.0000	
Classify Add dass Delete all Advanced -		70.0000 - 79.0000 - 79.0000	
Classify Add dass Delete all Advanced -			
Classify Add dass Delete all Advanced			
Classify Add dass Delete all Advanced •			
Classify Add dass Delete all Advanced •			
Classify Add dass Delete all Advanced			
Classify Add dass Delete Delete all Advanced			
		Classify Add class Delete Delete all	dvanced 🔻
Restore Default Style Save As Default Load Style Save Style 🔻	Restore Default Style	le Save As Default Load Style Save Style	•
OK Cancel Apply Help		OK Cancel Apply	Help

15. In the Symbol Selector dialog, click on Color selector.

×.	Symbol selector ? ×
Symbol layers	Unit Millimeter Transparency 0% Color Saved styles Corners diagonal dotted green land water wine
	Symbol 🔻
	OK Cancel

16. Click on a color fom the Select Color dialog.

🗏 Sele	ct Color X
Basic colors	
Custom colors	Hue: 0

17. Back in the Layer Properties dialog, you can click on the Label column next to each value and enter the text that you want to display. Similarly, you may click on the Range column to edit the selected ranges. Click OK once you are satisfied with the classes.

sa di	Layer Properties - newsweek_data ? ×
General	Style ▼ Layer rendering
Style Style	Layer transparency 0
abc Labels	Layer blending mode Normal Feature blending mode Normal
Fields	Craduated -
🤛 Display	Column LIFEXPCT 💌
Actions	Symbol Classes 3
Joins	Color ramp [source] Mode Quantile (Equal Count)
Diagrams	Symbol Value Label -99.0000 - 56.0000 LOW -90.0000 MEDIUM -90.0000 MEDIUM 70.0000 - 79.0000 HIGH -90.0000 -90.0000
	Classify Add class Delete Delete all Advanced T
Restore Default Style	e Save As Default Load Style Save Style 🔻
	OK Cancel Apply Help

18. This style definitely conveys a lot more useful map than the previous two attempts. There are clearly marked class names and colors to represent our interpretation of the life expectancy values.

